

Overhead Holders & Stops



Innovation, Quality,
Customer Service...

3400 Series Surface Mount, Medium Duty



Standard Features

- Surface mount
- Medium duty
- Side jamb mount for doors that do not extend to frame header
- Ideal for dressing room and washroom stall doors with frames
- Stop, hold-open and friction functions available
- Single acting doors only
- Non-handed
- Standard installation from 90° to 100° of opening (5° increments)
- Shock absorbing spring provides 3° to 5° cushion before dead-stop
- Standard fasteners supplied with sex bolts for 1-3/4" to 1-7/8" thick door (see options for other door thicknesses)
- Average weight per unit = 3 lbs.

Options Available

(see page B-5 for details)

- **THICK** - Fasteners for doors other than 1-3/4" to 1-7/8" thick - Specify door thickness
- **SEC** - Security fasteners
- **LL** - For lead-lined door applications
- **LS** - Less shock-absorbing spring for special applications
- **N** - All stainless steel (non-ferrous) components for wet environments to prevent corrosion
- **HC** - Hold closed
- **SPECIAL** - Contact ABH if the dimensions, hardware or specifications differ from what is shown on the template or if additional hardware is being used at the top of the door. A custom template and/or unit may be required.
- If using a closer, please go to our website and reference "ABH Overhead Holder & Stop Compatibility Chart" to determine possible conflict.

Material

- **Stainless steel** is the standard base material for arm, channel and jamb bracket for all finishes.

Door Frame Opening	Model Number		
Hinges	Hold Open	Stop	Friction
24" - 36"	3414	3424	3434

Specify When Ordering

- Model Number
- Finish
- Option(s), if applicable



Architectural Builders Hardware Manufacturing, Inc.
1222 Ardmore Avenue, Itasca, IL 60143
Tel: 630-875-9900 • Fax: 630-875-9918 / 800-932-9224
Web: www.abhmfg.com • Email: abhinfo@abhmfg.com