

## Options

### “AJB” - Angle Jamb Brackets

Available for most surface mount models – converts standard installation to pull side mount or push side flush mount mounting (see page B-3 for details).

They are also available separately, as a part.

- 44443 - 3300A & 4400 Series
- 70377 - 7000 Series
- 90541 - 8000, 9000 & 9000A Series

### “CL” - For Use with Cam Lift Hinges

Custom unit for use with cam lift hinges (½” maximum door lift)

### “HC” - Hold Closed

Special mechanism is integrated into the overhead stop holding the door closed at 0° and essentially doubling as a roller latch (available for stop function only). Hold-closed mechanism can be disengaged.

### “LL” - Lead Lined

Lead is provided to cover where mounting holes will pierce lead on lead-lined doors.

### “LS” - Less Spring

Typically used with a single point electronic door closer, overhead stop is supplied without the shock absorbing spring (stop function only).

### “N” - All Stainless Steel (Non-Ferrous) Components

Designed for use in wet environments - all stainless steel or non-ferrous components are provided with the unit, including all internal components and screws.

### “SEC” - Security Fasteners

Security fasteners are provided in lieu of standard fasteners for all exposed mounting holes – specify door and frame material when ordering.

### “SNB” - Sex Bolts

Sex bolt fasteners are added to 3500 series surface mount model screw pack, as they are not supplied standard.

### “T” - Threaded Pivot Screw and Nylon Washer in Lieu of Jamb Bracket

Typically used when space is limited in the frame head for installation or when installing a concealed model in an existing frame with minimal field prep.

### “THICK” - Door Thickness other than 1-¾”

Custom fasteners will be supplied to accommodate various door thicknesses other than 1-3/4” – specify door thickness.

### “SPECIAL” - Special Layout

ABH can provide custom units for countless non-standard applications. See page B-6 for order form or contact factory for assistance.

Overhead Holder Options - Compatibility Chart

| Series          |        | AJB | CL | HC | LL | LS | N | SEC | SNB | T | THICK | SPECIAL |
|-----------------|--------|-----|----|----|----|----|---|-----|-----|---|-------|---------|
| Concealed Mount | 1000   |     |    | ●  | ●  | ●  | ● | ●   |     | ● |       | ●       |
|                 | 1000A  |     |    | ●  | ●  | ●  | ● | ●   |     |   |       | ●       |
|                 | 1000SL |     |    |    | ●  | ●  | ● | ●   |     | ● |       | ●       |
|                 | 1000SA |     |    |    | ●  | ●  | ● | ●   |     |   |       | ●       |
|                 | 4000   |     |    | ●  | ●  |    | ● | ●   |     | ● |       | ●       |
| Surface Mount   | 3300A  | ●   | ●  | ●  | ●  | ●  | ● | ●   |     | ● | ●     | ●       |
|                 | 3400   |     |    | ●  | ●  | ●  | ● | ●   |     |   | ●     | ●       |
|                 | 3500   |     |    |    | ●  |    |   | ●   | ●   |   | ●     | ●       |
|                 | 4400   | ●   | ●  | ●  | ●  | ●  | ● | ●   |     | ● | ●     | ●       |
|                 | 7000   | ●   |    |    | ●  |    | ● | ●   |     |   | ●     | ●       |
|                 | HD7000 |     |    |    | ●  |    | ● | ●   |     |   | ●     | ●       |
|                 | 8000   | ●   |    |    | ●  | ●  |   | ●   |     |   | ●     | ●       |
|                 | 9000   | ●   | ●  | ●  | ●  | ●  | ● | ●   |     | ● | ●     | ●       |
| 9000A           | ●      | ●   | ●  | ●  | ●  | ●  | ● |     | ●   | ● | ●     |         |

